



The STC-400 series industrial monochrome camera provides excellent performance for machine vision solutions. The camera features high quality reproduction, a 1/2" high resolution IT CCD, electronic shutter to 1/10,000 of a second, HD/VD external sync input / output and a 12 pin connector for easy access of power, video signal and sync signals. The STC-400 is available in EIA and CCIR formats.

## Features:

- Fixed / Manual Gain
- Composite Outputs
- 1/2" IT CCD, 768(V) x 494(H)
- Electronic Shutter
- External Sync, (HD/VD)in/out
- Small size, Lightweight
- 570 TV Lines
- 12 pin Connector
- EIA & CCIR Formats
- 0.2 Lux Minimum Illumination
- 12VDC
- 'C' Mount

# STC-400/405 Industrial Camera

---

## Technical Specifications

---

### STC-400 / STC-405

- 768(H) x 494(V) 1/2" IT CCD (STC-400, EIA)
- 752(H) x 582(V) 1/2" IT CCD (STC-405, CCIR)
- Horizontal Frequency: 15.734khz (EIA), 15.625khz (CCIR)
- Vertical Frequency: 59.97Hz (EIA), 50.00Hz (CCIR)
- Sync System: Internal or HD/VD
- 2:1 Interlace / Non-Interlace
- Horizontal Resolution: 570 Lines
- Minimum Illumination: 0.2 Lux at F1.2 (AGC On)
- S/N Ratio: More than 56dB (AGC Off)
- Gamma: 0.45 / 1.0
- Pixel Clock Out
- Gain: Fixed, Manual Adjust
- Field / Frame Switchable
- Electronic Shutter 1/60-1/10,000 sec
- Video Output: 1.0p-p @ 75 ohms
- Power: 12 VDC
- Operating Temperature: -10degrees C to +40 degrees C (14F-104F)
- Weight: 20g (190g)
- Dimensions: 31(W) x 29(H) x 73(D)

The logo for Sentech, featuring the word "SENTECH" in a bold, blue, sans-serif font. The letters "S", "E", and "N" are larger and more prominent than the others, and the "T" and "E" are connected.

Sensor Technologies America Inc.

1015 North I-35E #206 Carrollton, TX 75006

Phone: 972-245-4243 Fax: 972-446-0056

Toll Free 877-736-8324 (877-SENTECH)

Website: [www.SentechAmerica.com](http://www.SentechAmerica.com)

\*STC-SS400 Remote Head Format also Available